

Technical specifications

Print technology	HP Thermal Inkjet
Print head nozzles	304
Technology resolution	HP Color Layering technology, Photoret IV
Number of inks	6 (cyan, magenta, yellow, black, light cyan, light magenta)
Ink type	HP Vivera dye-based inks
Ink drop-size	4pl
Lightfastness	82 years Wilhelm Imaging Research, Inc. concluded that prints made with HP 85 Ink Cartridges and HP Premium Plus Photo Papers may be displayed indoors under glass for 82 years before noticeable fading and staining occur (see www.wilhelm-research.com for details).
Print speed	Colour Image (ISO N5) Normal Mode A3 Glossy Paper: 4 min / page The printed area dimensions (margins not included) for file N5 are 279.9 x 350 mm. Colour Image (ISO N5) Normal Mode A2 Glossy Paper: 6.3 min / page The printed area dimensions (margins not included) for file N5 are 368 x 460 mm.
Print quality	2400 x 1200 dpi
Line accuracy	± 0.2%
Minimum line width	0.04 mm
Memory	64 MB
Media types	Paper (plain, inkjet, coated, heavyweight coated, semi-gloss, glossy, proofing, photo, brochure/flyer), transparencies
Media sizes	A2, A3, A4, B3, B4, A/B/C (English architectural), envelopes, banners Custom: 76 x 142 to 458 x 1625 mm
Print margins	Roll: 5 mm on all sides; Sheet: top: 5 mm, bottom: 12 mm, left: 5 mm, right: 5 mm
Maximum media length	Roll: HP Designjet 90 Printer: 45.7 m with optional roll-feed; HP Designjet 90r/gp Printer: 45.7 m Sheet: 1625 mm
Maximum media width	458 mm
Maximum print length	15.24 m (application dependent)
Maximum print area	448 x 1608 mm
Media handling	Sheetfed (input tray, manual single-sheet feed, rear path), roll-feed with automatic cutter (optional on HP Designjet 90 Printer)
Media thickness	Up to 0.4 mm through Rear Path
Media weight	Up to 300 g/m ² through Rear Path
Interface and connectivity	Standard: USB 1.1 (USB 2.0 compliant), Centronics parallel IEEE-1284 (ECP compliant), 1 EIO slot Optional: HP Jetdirect 620n, 615n, 680n, 610n, 600n, 175x, 310x, 380x, en3700 Drivers included: Raster driver for Mac OS 9.x, 10.2, 10.3; PCL 3-GUI Windows* driver; Microsoft* Windows drivers 95, 98, Me, NT 4.0, 2000, XP including support for AutoCAD 2000, USB, and ECP drivers
Control panel	2 LEDs for status: Power, Attention; 3 keys: Power, Cancel, OK; display area containing information icons
Operating systems compatibility	Microsoft* Windows* 98 SE, Me, 2000, XP; Mac OS 9.x, 10.2, 10.3
Minimum system requirements	Microsoft* Windows* 98: Pentium* I, 133 MHz, 128 MB RAM, 300 MB available hard disk space; Microsoft Windows 2000, Server 2003: Pentium II, 300 MHz, 128 MB RAM, 400 MB available hard disk space; Microsoft Windows XP: Pentium III, 733 MHz, 256 MB RAM, 400 MB available hard disk space iMac G3, Mac OS 9 v 9.1, Mac OS 10 v 10.2, 256 MB RAM, 100 MB available hard disk space
Recommended system requirements	Microsoft* Windows* 95, Me: Pentium* II, 300 MHz, 128 MB RAM, 1 GB available hard disk space; Microsoft Windows 2000: Pentium III, 733 MHz, 256 MB RAM, 2 GB available hard disk space; Microsoft Windows XP: Pentium IV, 1 GHz, 256 MB RAM, 2 GB available hard drive Mac OS 9 v 9.2, Mac OS 10 v 10.2 and higher, 10.3, G3 dual processor, 512 MB RAM, 1 GB available hard disk space
Printer languages	PCL 3-GUI RGB 24-bit Contone Optional: Adobe* PostScript* 3™ via optional EFI Designer Edition software RIP
Drivers included	Raster driver for Mac OS 9.x, 10.2, 10.3; PCL 3-GUI Windows* driver; Microsoft* Windows drivers 95, 98, Me, NT 4.0, 2000, XP including support for AutoCAD 2000, USB, and ECP drivers
Software included	HP Designjet Windows* software, HP Designjet Macintosh software
Power	Requirements: Input voltage 100 to 240 VAC (± 10%) auto range, 50/60 Hz (± 3 Hz), 2 amp maximum Supply type: Built-in universal power supply Consumption: 65 watts maximum
Dimensions (w x d x h)	Out of package: HP Designjet 90 Printer: 890 x 415 x 220 mm, HP Designjet 90r/gp Printer: 890 x 520 x 220 mm
Weight	Out of package: HP Designjet 90 Printer: 18.5 kg; HP Designjet 90r/gp Printer: 19.5 kg
Operating environment	Environmental ranges: operating temperature: 5 to 40° C; recommended operating temperature: 15 to 35° C; operating humidity: 20% to 80% RH; recommended operating humidity: 25% to 75% RH; storage temperature: -25 to 55° C; storage humidity: 0% to 95% RH
Certifications	Compliance for Class B products, Class A when connected to LANs: EU (EMC Directive), USA (FCC rules), Canada (DoC), Australia (ACA), New Zealand (MoC), China (CCC), Japan (VCCI); Class A: Korea (MIC), Taiwan (BSMI) IEC 950-compliant, EU LVD and EN60950 compliant, CSA certified for US and Canada, Mexico NOM-1-NYCE, Argentina IRAM, China CCC, Singapore PSB, Russia VNIIS, Korea KTL Energy star®
Warranty	One-year next-business-day exchange

Ordering information

Q6656A	HP Designjet 90 Printer, power cord, USB cable, printheads (6), print cartridges (6), input/output tray, input tray cover, driver & documentation CD, setup Poster, quick reference guide, media samples, customer service guide
Q6656B	HP Designjet 90r Printer, as Q6656A plus roll feed and spindle assembly
Q6656C	HP Designjet 90gp Printer, as Q6656B plus HP colorimeter with display profiling and calibration software plus ICC profiles, powered by GretagMacbeth™ technology
Accessories	
Q6662A	HP Designjet 90 Roll Feed accessory
Q6661A	HP Designjet 90 Spindle accessory
Q6641C	EFI Designer Edition 4.2 for HP M International
Q6643C	EFI Designer Edition 4.2 for HP XL International
Media supplies	
Q1961A	HP Coated Paper 90 g/m ² – A2+/100 sheet (458mm x 610mm)
Q5492A	HP Photo Matte 196 g/m ² – A3+/50 sheet (330mm x 483mm)
Q1967A	HP Proofing Matte 146 g/m ² – A3+/100 sheet (330mm x 483mm)
Q5486A	HP Premium Plus Photo and Proofing Gloss 286 g/m ² – A2+/25 sheet (330mm x 483mm)
Q5487A	HP Premium Plus Photo and Proofing Gloss 286 g/m ² – A2+/20 sheet (458mm x 610mm)
Q5489A	HP Premium Plus Photo Satin 286 g/m ² – A3+/25 sheet (330mm x 483mm)
Q5490A	HP Premium Plus Photo Satin 286 g/m ² – A2+/20 sheet (458mm x 610mm)
C7884A	HP Proofing Semi-gloss 150 g/m ² – A3+/50 sheet (330mm x 483mm)
Q7970A	HP Proofing Semi-gloss Contract Proofing Paper 235 g/m ² – A3+/50 sheets (330mm x 483mm)
Q7895A	HP Proofing Semi-gloss – 150 g/m ² – 18" roll* (458mm x 30.5m)
Q7896A	HP Proofing Matte 146 g/m ² – 18" roll* (458mm x 30.5m)
Q7897A	HP Coated Paper 90 g/m ² – 18" roll* (458mm x 45.7m)
Q7920A	HP Premium Plus Photo Satin 286 g/m ² – 18" roll* (458mm x 15m)
*Roll works only with roll feed, which is optional on the base model and standard on r and gp models	
Ink supplies	
HP 85	Cyan, Magenta, Yellow, Light Cyan, Light Magenta printheads and cartridges
HP 84	Black printheads and cartridges
Multipack	All cartridges also available in 3-ink multipack
Service and support	
U3477A/E	HP Care Pack, next business day on-site response, 3 years
U4662PA/PE	HP Care Pack, post warranty, next business day on-site response, 1 year

<http://www.hp.com> <http://www.hp.com/go/designjet>

For more information, please call your local HP sales office or representative: **Albania:** +49 89 9396 1803; **Algeria:** +213 (0) 61 68 23 00; **Austria:** +43 (0) 810 00 60 80; **Bahrain:** 800 171; **Belgium:** +32 (02) 729 71 11; **Bulgaria:** +359 2 960 19 40; **Bosnia-Herzegovina:** +49 89 9396 1803; **Commonwealth of Independent States (CIS):** +(095) 923 50 01; **Croatia:** +385 1 606 02 00; **Czech Republic:** +420 261 108 108; **Denmark:** +45 48 12 10 00; **HP East Africa, Authorized Consultant:** +254 20 27 16 111; **Egypt:** HP +202 792 5070; **Estonia:** +372 6 813 820; **Finland:** HP Myyntipalvelu 010 217 2700; **France:** +33 (0) 826 800 400; **Germany:** +49 (0) 180 532 62 22; **Greece:** +30 801 11 22 55 47; **Hungary:** +36 (1) 382 11 11; **Iceland:** +354 (1) 67 10 00; **Ireland:** +353 1 615 82 00; **Israel:** +972 9 830 48 48; **Italy:** Prodotti +39 02 92607 330, Servizio HP Care Pack: +39 02 9212 2040; **Kazakhstan & Kyrgyzstan:** +7 327 2 58 43 43; **Latvia:** +371 703 07 00; **Lithuania:** +370 5 2103 300; **Luxembourg:** (+352) 263 160 34; **Macedonia:** +49 89 9396 1803; **Malta:** +49 89 9396 1803; **Middle East (Within UAE Toll Free):** 800 45 20; **Moldova:** +49 89 9396 1803; **Morocco (African Region):** Call Centre +212 22 40 47 47, HP Sale Office +212 22 97 37 37/+212 22 43 64 00; **Netherlands:** 0800 266 7272; **Nigeria:** +234 13 205 241/3; **Norway:** +47 24 09 70 00; **Poland:** 0 801 522 622 and/or 00 48 565 77 00 (calls are charged at national rates); **Portugal:** +351 808 200 808 (end user welcome desk for commercial products); **Romania:** +40 (21) 303 83 00; **Saudi Arabia:** (Toll free) 800 897 14 33, Office Number: +96612731200; **Serbia and Montenegro:** +381 11 201 99 00; **Slovakia:** 0800 147 147; **Slovenia:** +386 1 230 74 20; **Spain:** +34 (91) 631 16 00; **Sweden:** +46 200 27 00 00; **Switzerland:** Pre-sales/product information +41 (0) 848 88 44 66, Spare parts, manuals +41 (0) 848 84 74 64; **Tunisia:** +216 1 89 12 22; **Turkey:** +90 (216) 579 79 00; **UAE (Toll Free):** 800 45 20 or 800 49 10; **Ukraine:** +380 44 490 61 20; **United Kingdom:** HP Teleweb Glasgow +44 (0) 845 270 40 00



©2005 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 09/05 5983-1206E2E

